

Item	115VAC Motor	230VAC Motor
Type	OEM Replacement	HVAC 3.3" Diameter Motor
Motor Type	Shaded Pole	Permanent Split Capacitor
Enclosure	Totally Enclosed Fan-Cooled	Totally Enclosed Air-Over
Duty	---	Continuous Air-Over
HP	1/15	1/15
Nameplate RPM	1550	1550
Voltage	115	208-230
NEMA/IEC Frame	Non-standard	Non-Standard
Service Factor	1	1
Full Load Amps	2.3A	0.5-0.45A
Hz	60	60/50
Rotation	CCWSE	CW/CCW
Insulation Class	B	B
Ambient (C)	40	40
Number of Speeds	---	1
Mounting	Stud	Stud
Bearings	Sealed Ball Bearing	Ball
Thermal Protection	Auto	Auto
Body Dia. (In.)	4	3.3
Shaft Dia. (In.)	5/16	5/16
Shaft Length (In.)	2 3/8	2
Length Less Shaft (In.)	4	3 1/4
Stud Location	4/SE	4/BE
Stud/Base Mtg. Pattern (In.)	2 7/8	2 x 2
Phase	1	1
RPM Range	1400-1800	1400-1800
Shaft Type	---	Flat
Capacitor Required	---	Included
Includes	---	3 MFD 370 VAC Capacitor
Agency Compliance	UL Recognized, CSA Certified	UL Recognized (E47479), CSA Certified (227508)
Mounting Pattern	---	2 x 2

Five Boynton Road Hopping Brook Park Holliston, MA 01746 USA  
 TEL: 508-429-1110 FAX: 508-429-7433 WEB: www.walchem.com

P/N 180443.B April 2012